

LANCOM SPSU UF-760

Hot-swappable power supply unit for Unified Firewall UF-760

A constant power supply for your firewalls is indispensable in business-critical network environments. The hot-swappable SPSU UF-760 power supply unit therefore guarantees maximum reliability for your LANCOM R&S®Unified Firewall UF-760. Your advantage: The power supply unit can be replaced during operation to ensure consistent network security.

- 300 watts power supply unit
- Improved failover of the LANCOM R&S®Unified Firewall UF-760
- Hot-swappable—can be inserted during operation
- Input voltage: 115 VAC and 230 VAC
- Output voltage: +12 V @25 A, +5 VSB @3 A
- Over current protection
- Over voltage protection
- Short circuit protection
- Operating temperature: 0°C to 50°C

LANCOM SPSU UF-760

Technical Information

Input voltage	100 - 240 VAC, 50 - 60 Hz
Current consumption	5 A @115 VAC, 2,5 A @230 VAC
Output power	300 W
Output voltage	+12 V @25 A, +5 VSB @3 A

Mechanical Information

Operating temperature	0°C to 50°C
Storage temperature	-20°C to 80°C
Operating humidity range	20-80% RH, non-condensing

Scope of delivery

Documentation	Installation instruction
---------------	--------------------------

Support

Warranty	2 years support
----------	-----------------

Further information

Supported devices	→ LANCOM R&S®Unified Firewall UF-760, item number: 55035
-------------------	--

Item number(s)

SPSU UF-760	55148
-------------	-------